

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 037 461 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
20.09.2000 Bulletin 2000/38

(51) Int. Cl.⁷: H04N 5/445

(21) Application number: 00104896.6

(22) Date of filing: 08.03.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Holme, Richard
Cookridge, Leeds LS16 7DB (GB)

(74) Representative: Wood, Graham
Bailey Walsh & Co,
5 York Place
Leeds LS1 2SD (GB)

(30) Priority: 16.03.1999 GB 9905968

(71) Applicant:
Pace Micro Technology PLC
Shipley, West Yorkshire BD18 3LF (GB)

(54) Programme guide display

(57) A display (2) is generated for viewing on a display screen. The display (2) indicates any or any combination of a function of the display screen control parameters and/or information relating to channels and/or programmes which can be viewed on the screen. The display further comprises one or more geometrical shapes, each split into a plurality of segments (4, 8, 14, 18; 24, 26, 28; 40, 42, 44) and the segments (4, 8, 14, 18; 24, 26, 28; 40, 42, 44) represent particular time intervals, programme/channel information, control parameter information or the like.




FIG. 1




FIG. 2

EP 1 037 461 A2

BEST AVAILABLE COPY

Description

[0001] The invention which is the subject of this application relates to a format for the display on a television or monitor screen to represent information to the user of the screen relating to material which is to be displayed on the said screen. In particular, but not necessarily exclusively, the invention relates to the generation of a display for use as part of an electronic programme guide to the user which indicates to the user the various options of programmes which can be watched at that time and/or in the future on the various channels and/or broadcast services available to the user.

[0002] The provision of electronic programme guide (EPG) information to a user of a display screen linked to broadcast data receiving apparatus is well known. The data for the EPG is typically generated from data which is broadcast from a remote location and relates to the various channels and programmes which are available or selection by the user of the apparatus. The data for the EPG is broadcast and transmitted along with the video, audio and/or text data to broadcast data receiving apparatus located in premises and which apparatus is connected to displays. The data transmission can be by satellite, cable or terrestrial network systems.

[0003] As the proliferation of available channels and programmes which can be selected increases so there is a need to display this information to the user but, as the number of channels and programmes which are available to the user increase so it becomes increasingly difficult to either show information for a relatively large time interval and/or show all of the programme channels on the screen at any one time.

[0004] The aim of the present invention is to provide for the generation of and a display to a user which represents in an easily distinguishable and interpretable manner, information relating to programmes which can be viewed at that time or in the future. It is a further aim of the invention to provide a display which can be generated to display functions other than programmes such as for example volume settings, contrast or brightness settings on the functions of the television set and/or signal receiver.

[0005] In a first aspect of the invention there is provided a process for generating a display for viewing on a display screen, said display generated by broadcast data receiving apparatus provided in connection with the display screen and said display including information generated from any, or any combination of data held in the memory of the apparatus and/or data broadcast to the apparatus from a remote location, and indicating programme information relating to a programme channel and characterised in that said display includes a geometrical shape split into a plurality of segments.

[0006] The invention therefore provides a display which is generated for viewing on a display screen by broadcast data receiving apparatus, said display indicating any or any combination of a function of the display screen control parameters and/or information relating to channels and/or programmes which can be viewed on the screen and wherein said display comprises a geometrical shape split into a plurality of segments.

play screen control parameters and/or information relating to channels and/or programmes which can be viewed on the screen and wherein said display comprises a geometrical shape split into a plurality of segments.

[0007] In one embodiment each geometrical shape represents a particular time interval on one programme channel and the segments of said geometrical shape are selected to represent programmes which occur on that channel during the particular time interval. The size of the segment indicates the length of the particular programme and hence each of the programmes in that time interval so that the user has an immediate indication of the programmes available to watch on the channel represented by the geometrical shape and over the time represented by the geometrical shape.

[0008] In one embodiment, a plurality of geometrical shapes can be generated either at the same time on the display screen to represent the programmes available to watch on some or all of the available channels on the same screen or alternatively, individual geometrical shapes can be provided in sequence for display to the user and controlled by the user using display control means such as a conventional remote control device so that the same can be "flicked through" by the user.

[0009] In one embodiment, the segments can be coloured or provided of differing colours or patterns to distinguish the same. In one embodiment the segments can be colour coded so as to further indicate the subject matter of the programmes in question so that certain areas of interest such as nature, sport etc, can be represented by specified colours and the data which allows the appropriate colours or patterns to be input is broadcast along with the programme data to the broadcast data receiving apparatus which then separates the data and generates the appropriate segment colour or pattern.

[0010] It is envisaged that in a typical embodiment the broadcast data receiving apparatus will have in memory data which controls the generation of the shape and the generation of segments of the shape. However the actual configuration of the segments within the shape is determined by data received from the broadcaster. This data can include programme start and end times, locates the programme data on a particular channel, can include information relating to the programme subject matter and so on. When this data is received and the user selects to view the programme information the geometrical shape is generated and the positioning of the segments determined with respect to the received data and the programmes which can be viewed on the channel represented by the shape and over the time interval represented.

[0011] In a yet further embodiment of the invention, as time progresses there can be progressive shading, movement of the display or portions of the display, or otherwise altering the geometrical shape of the display to indicate the passage of time through the time interval

displayed on the geometrical shape if the geometrical shape is indicating presently available programmes.

[0012] In a further aspect of the invention there is provided a process for generating a display for viewing on a display screen, said display generated by broadcast data receiving apparatus provided in connection with the display screen and said display including information generated from data relating to the display screen and broadcast data receiving apparatus and representing a function of operation of the display screen or broadcast data receiving apparatus and characterised in that said display includes a geometrical shape split into a plurality of segments.

[0013] In one embodiment the shape represents a range of volume and a change in appearance of the shape or segments indicates the volume level selected.

[0014] Typically a plurality of geometric shapes, in combination, represent the range of volume.

[0015] Thus, in this embodiment, the geometrical shape can still be split into a series of segments and indications which can be representative of a function or functions of the operation of the display are provided such as the display of a television set, such that for example the geometric shapes may indicate the range of volume which is possible by a series of segments and the selection of a particular volume level is indicated by a change in appearance of segments from zero to the particular volume level selected.

[0016] In whichever embodiment it is envisaged that the geometric shape best suited would be a circle but the invention can equally be applied in triangles, squares, rectangles, hexagonal shapes, ellipses, semi-circles.

[0017] Specific embodiments of the invention will now be described with reference to the accompanying drawings, wherein:-

Figure 1 illustrates a first embodiment of the invention;

Figure 2 illustrates a further embodiment of the invention;

Figure 3 illustrates a yet further embodiment of the invention; and

Figures 4A to 4D illustrate a further aspect of the invention in relation to television and/or set top box control displays.

[0018] Referring firstly to Figure 1, there is illustrated a display in accordance with the invention for indicating to a user the current status and programmes available to view over a period of time and, in the case of Figure 1, on one particular channel. Thus, in the Figure 1, there is illustrated a display 2 for generation on a television screen or monitor screen. The display is circular and is split into a series of segments. In this case, the

display represents 60 minutes through 360° with the vertical line 4 indicating the start and finish of the 60 minutes. The first segment 6 is left blank but may alternatively be shaded in a distinctive manner to indicate via the line 7 to the user the time at which they are actually viewing the display with respect to the start of the hour. Thus, the line 7 progresses around the circle and the size of the segment 6 increases as time progresses during the hour. The segment 8 represents to the user the remaining time of programme 1 which will finish as indicated by the line 10, and therefore the user will be aware that they have missed the start of programme 1 but still have a period of time of just less than half of the programme to view. The segment 14 indicates the duration of programme 2 and the following segment 18 the duration of programme 3 and so it will be appreciated that Figure 1 illustrates a simple, clearly distinguishable and descriptive display to the user with respect to the three programmes which can be viewed within the hour during which the user is looking at the display.

[0019] Figure 2 illustrates an alternative embodiment wherein the display is again circular in form and again comprises a series of segments 24, 26, 28, each of which represents programmes 1, 2 and 3 as with Figure 1. In this case however there is superimposed a clock face 30 with hands 32, 34. It will therefore be appreciated that if the display of Figure 2 is to represent an hour as with figure 1, then the hand 32 illustrates the same time of viewing as does the line 7 in Figure 1. However, as an alternative, the display of Figure 2 can be used to represent a 12-hour period of time and so will include a significantly increased number of segments with both the hands 32 and 34 indicating to the user the particular time of viewing and allowing the user to cross-reference the time with the programme sectors to allow them to decide what and when to watch.

[0020] In one embodiment a series of said geometrical shapes can be generated for different channels so that these can be scrolled through on the display screen using conventional scrolling means or alternatively, a series of the displays can be presented on one screen display for viewing.

[0021] Figure 3 illustrates a yet further embodiment which is broadly in line with the features of Figure 2 in that at the outer edge, programmes 1, 2 and 3 are indicated by the sectors 40, 42 and 44. Furthermore the hands 32, 34 are used in a similar manner to that described in Figure 2 and reference to Figure 2 describes the operation of the outer sector of Figure 3. However, there is also shown an inner sector 46 which also comprises a series of segments 48 to 58 and these inner segments represent a 12-hour period of time so that in one display for one channel, there is provided a 1-hour display on the outer sector of segments and a 12-hour display on the inner sector with the large hand 32 being relevant to the outer sector time and the inner hand 34 being relevant to the inner sector time, thereby providing to the user an immediate indication of pro-

grammes which are immediately available to watch or will be available within the next hour and also allow them to plan their viewing schedule for the next 12 hours.

[0022] Figures 4A to 4D illustrate a further aspect of the invention wherein geometrical displays are used to indicate the particular level of controls of a television set or broadcast data receiver or monitor so that for example any, or any combination of the displays shown in Figures 4A to 4D can be used to represent any or any combination of the level of volume, brightness, contrast or colour of the television monitor display to the user and in this embodiment the data used to generate the display is obtained from memory of the display screen, such as that of a television set and/or the broadcast data receiver. This differs from the embodiment where the generation of geometrical shapes is undertaken to indicate programme information as this is typically generated wholly from data received by the broadcast data receiver from a remote location, or in combination with data held in memory, as the display is generated to show real time or future time information to the user and requires to receive updates on this information on an ongoing basis which is transmitted to the receiver apparatus which decodes, identifies and processes the relevant digital data and, from this received data, the size and representation of the segments of the shapes can be generated at each time the user request the generation of the programme information display.

Claims

1. A process for generating a display (2) for viewing on a display screen, said display (2) generated by broadcast data receiving apparatus provided in connection with the display screen and said display including information generated from any, or any combination of data held in the memory of the apparatus and/or data broadcast to the apparatus from a remote location, and indicating programme information relating to a programme channel and characterised in that said display includes a geometrical shape split into a plurality of segments (4, 8, 14, 18; 24, 26, 28; 40, 42, 44).
2. A process for generating a display according to claim 1 characterised in that the geometrical shape represents a particular time interval of a specific programme channel which can be selected to be viewed via the display screen.
3. A process for generating a display (2) according to claim 2 characterised in that the segments (4, 8, 14, 18; 24, 26, 28; 40, 42, 44) converge at a common point on the display and diverge outwardly therefrom.
4. A process for generating a display (2) according to claim 3 characterised in that the size of each seg-

ment (4, 8, 14, 18; 24, 26, 28; 40, 42, 44) with respect to the geometrical shape and the time interval represented, indicates the length in time of a programme which that segment represents.

5. A process for generating a display (2) according to claim 1 characterised in that a plurality of geometrical shapes are generated on the display screen, each shape representing a user selectable channel.
6. A process for generating a display (2) according to claim 1 characterised in that a plurality of geometrical shapes are generated in succession to allow the user to view the same in sequence on screen using a display control means.
7. A process for generating a display (2) according to claim 1 characterised in that the segments (4, 8, 14, 18; 24, 26, 28; 40, 42, 44) are coloured and/or patterned to visually distinguish adjacent segments.
8. A process for generating a display (2) according to claim 1 characterised in that the segments (4, 8, 14, 18; 24, 26, 28; 40, 42, 44) are colour coded to indicate to the user who has access to the key to the coding, the subject matter of the programmes represented by the respective segments.
9. A process for generating a display (2) according to claim 1 characterised in that as time progresses, there is progressive shading of the geometrical shape and segments to indicate those programmes which have been shown and those which are to be displayed in the future.
10. A process for generating a display (2) according to claim 1 characterised in that as time progresses the shape of the geometrical shape or segments of the shape change to indicate the time change.
11. A display (2) according to claim 1 characterised in that the geometric shape includes any or any combination of circles, triangles, squares, rectangles, hexagonal shapes, ellipses, semi-circles.
12. A display (2) according to claim 1 characterised in that the geometrical shape is a circle with numbers at spaced intervals representing hours to depict a clock face (30) with hands (32, 34), said hands representing the progression of time with respect to programmes represented by segments of the shape.
13. A process for generating a display (2) for viewing on a display screen, said display (2) generated by broadcast data receiving apparatus provided in connection with the display screen and said display

including information generated from data relating to the display screen and broadcast data receiving apparatus and representing a function of operation of the display screen or broadcast data receiving apparatus and characterised in that said display includes a geometrical shape split into a plurality of segments (4, 8, 14, 18; 24, 26, 28; 40, 42, 44). 5

14. A process for generating a display (2) according to claim 13 characterised in that the shape represents a range of volume and a change in appearance of the shape or segments (4, 8, 14, 18; 24, 26, 28; 40, 42, 44) indicates the volume level selected. 10
15. A process for generating a display in accordance with claim 14 characterised in that a plurality of geometric shapes, in combination, represent the range of volume. 15

20

25

30



35

40

45

50

55






FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.